### **APPENDIX B**

## SOUTH LAKE TAHOE GROUNDWATER FLOW MODEL



# Simulation of Lake-Groundwater Interaction, South Lake Tahoe, California



## September 2003

#### Prepared for:

US Army Corps of Engineers, Sacramento District, Environmental Engineering Branch 1325 J. St., Sacramento, CA 95814

# Simulation of Lake-Groundwater Interaction, South Lake Tahoe, California

September 2003

#### Prepared for:

US Army Corps of Engineers, Sacramento District, Environmental Engineering Branch 1325 J. St., Sacramento, CA 95814

U.S. Army Corps of Engineers, Hydrologic Engineering Center 609 Second St, Davis CA 95616 (530) 756-1104

#### **ACKNOWLEDGEMENTS**

Construction and calibration of the South Lake Tahoe groundwater flow model was performed by Jon Fenske and Mak Shatila of the U.S. Army Corps of Engineers, Hydrologic Engineering Center (HEC). The Project Manager for this study is Phillip Brozek of the U.S. Army Corps of Engineer, Sacramento District. Assistance with site conceptualization was provided by Lewis Hunter and Tim Crummett of the U.S. Army Corps of Engineers, Sacramento District. Data was provided by Meegan Nagy and Melissa Kieffer of the U.S. Army Corps of Engineers, Sacramento District. The authors of this document are Jon Fenske and Mak Shatila of HEC.

## **TABLE OF CONTENTS**

List of Figures.	1V
List of Tables.	V
1. Introduction	1
2. Site Description.	1
3. Prior Groundwater Modeling Studies.	3
4. Data Analysis	4
5. Development of Groundwater Flow Model	6
6. Model Calibration.	12
7. Model Application	13
8. Sensitivity Analysis	15
9. Conclusions and Recommendations	17
10. References	18

## LIST OF FIGURES

Figure 1	Study area
Figure 2	Representation of boundary conditions
Figure 3	(a) Lakebed elevation at south Lake Tahoe and (b) lakebed elevation simulated by model
Figure 4	Representative profile of General Head Boundary (GHB) configuration used to simulate lake-groundwater interaction23
Figure 5	Representation of layer 1 hydraulic conductivity (K <sub>h</sub> ) used in model
Figure 6	Representation of layer 2 hydraulic conductivity (K <sub>h</sub> ) used in model
Figure 7	Representation of layer 3 hydraulic conductivity (K <sub>h</sub> ) used in model
Figure 8	Representation of layer 4 hydraulic conductivity (K <sub>h</sub> ) used in model
Figure 9	Representation of layer 5 hydraulic conductivity (K <sub>h</sub> ) used in model
Figure 10	Representation of layer 6 hydraulic conductivity (K <sub>h</sub> ) used in model
Figure 11	Delineation of south Lake Tahoe shoreline and tables of total and net fluxes per region for various scenarios27
Figure 12	Side-view representation of "high discharge conditions" water exchange between groundwater and south Lake Tahoe 28
Figure 13	Side-view representation of "low discharge conditions" water exchange between groundwater and south Lake Tahoe28
Figure 14	Side-view representation of effect of GHB boundary conceptualization on water exchange between groundwater and south Lake Tahoe

## LIST OF TABLES

Table 1	Hydraulic conductivity units	11
Table 2	Sensitivity of simulated groundwater discharge to hydrologic parameters	15
Table 3	Sensitivity of simulated groundwater discharge to lake elevation.	15